## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Menu A/S
--------------------------------	----------

**Supplier's address:** PD, Aarhusgade 130, 2150 Nordhavn -, DK

Model identifier: 2610039 E27, DTW 95

<b>T</b>	- 6	10 - 1- 1		
IVna	$\alpha$ T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Type of light so	uice.			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	o-type	Screw cap E27		
(or other electr	ic interface)			
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
	mption in on- 100 h), rounded st integer	4	Energy efficiency class	F
indicating if it r in a sphere (3 cone (120º) or i (90º)	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	20002700
On-mode prespressed in W	oower (P <sub>on</sub> ),	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer	Height	135	Spectral power	See image
dimensions	Width	95	distribution in the	in last page
without	Depth	95		 

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	45	
		Chromaticity	0,470	
		coordinates (x and y)	0,420	
Parameters for LED and OLED light sources:				
R9 colour rendering index value 75 Survival factor 0,90		0,90		
the lumen maintenance factor 0,95				

(a)'-': not applicable; (b)'-': not applicable;